

In the Claims:

All of the currently pending claims are listed below including any amendments proposed herein. Please amend the claims as follows:

1. (Original) A display device, comprising a substratum and all-metal electronics formed on a surface of the substratum and operable to control operation of a plurality of basic visible elements associated with the substratum.
2. (Original) The display device of claim 1 wherein the substratum comprises one of glass, plastic, metal, silicon, silicon nitride, silicon oxide, or polyimide.
3. (Original) The display device of claim 1 wherein the substratum is part of a rigid assembly, a foldable assembly, or a flexible assembly.
4. (Original) The display device of claim 1 wherein the display device is one of transmissive, reflective or emissive.
5. (Original) The display device of claim 1 wherein an image generated by the display device is one of directly viewed or projected.
6. (Original) The display device of claim 1 wherein each of the plurality basic visible elements comprises a pixel, and each pixel comprises a plurality of subpixels.
7. (Original) The display device of claim 6 wherein the all-metal electronics are operable to control operation of each of the subpixels independently.

8. (Original) The display device of claim 1 wherein the all-metal electronics comprise a plurality of transpinnors, each transpinnor comprising a network of multi-layer thin-film elements, at least one thin-film element in the transpinnor exhibiting giant magnetoresistance, the transpinnor further comprising a conductor magnetically coupled to the at least one thin-film element for controlling operation of the transpinnor, wherein the transpinnor is operable to generate an output signal which is a function of a resistive imbalance among the thin-film elements and which is substantially proportional to a power current in the network of thin-film elements.

9. (Original) The display device of claim 8 wherein the plurality of transpinnors includes first transpinnors configured as switches, at least one of the first transpinnors being associated with each of the basic visible elements and being operable to control operation of the associated basic visible element.

10. (Original) The display device of claim 9 wherein the plurality of transpinnors includes second transpinnors configured as digital-to-analog converters (DACs), at least one of the DACs being associated with each of the basic visible elements and being operable to provide a control signal to the at least one first transpinnor corresponding to the associated basic visible element.

11. (Original) The display device of claim 10 further comprising a plurality of blocks of all-metal memory, at least one of the blocks of memory being associated with each of the basic visible elements and being operable to store image data for use by the at least one DAC corresponding to the associated basic visible element.

12. (Original) The display device of claim 11 wherein each basic visible element comprises a pixel comprising a first number of subpixels, and wherein the at least one first transpinnor comprises the first number of first transpinnors, the at least one DAC comprises the first number of DACs, and the at least one block of memory comprises the first number of blocks of memory, each subpixel corresponding to and being controlled by one of the first transpinnors, one of the DACs, and one of the blocks of memory.

13. (Original) The display device of claim 12 wherein each of the memory blocks is operable to store a plurality of bits of the image data.

14. (Original) The display device of claim 11 wherein the plurality of blocks of memory comprises frame memory and the image data comprise frame data.

15. (Original) The display device of claim 11 wherein the first transpinnors, the DACs, and the memory blocks are arranged in a plurality of stacked levels of the all-metal electronics.

16. (Original) The display device of claim 11 wherein the at least one first transpinnor, the at least one DAC, and the at least one memory block associated with each basic visible element are disposed in multiple layers of all-metal circuitry and comprise one of a plurality of interchangeable circuit modules.

17. (Original) The display device of claim 1 wherein the all-metal electronics comprise control switches for directly controlling operation of the basic visible elements, digital-

to-analog converters (DACs) for converting image data to control the control switches, frame memory for storing the image data, and selection circuitry for enabling individual ones of the basic visible elements.

18. (Original) The display device of claim 17 wherein the all-metal electronics further comprise system memory for a computing system associated with the display device.

19. (Original) The display device of claim 18 wherein the system memory comprises graphics memory, main memory, and mass storage memory.

20. (Original) The display device of claim 18 wherein the all-metal electronics further comprises processing circuitry for carrying out processing functions of the computing system.

21. (Original) The display device of claim 20 wherein the processing circuitry comprises a memory controller, a graphics controller, and a central processing unit.

22. (Original) The display device of claim 17 wherein the frame memory comprises a plurality of memory cells, each memory cell comprising a multi-layer structure exhibiting magnetoresistance.

23. (Original) The display device of claim 22 wherein each multi-layer structure comprises:

a plurality of magnetic layers, at least one of the magnetic layers being for magnetically storing one bit of information; and

a plurality of the access lines integrated with the plurality of magnetic layers and configured such that the bit of information may be accessed using selected ones of the plurality of access lines and the giant magnetoresistive effect;

wherein the magnetic layers are part of a substantially closed flux structure.

24. (Original) The display device of claim 22 wherein the plurality of memory cells are arranged in a plurality of substantially identical and interchangeable memory array modules.

25. (Original) The display device of claim 24 wherein each memory array module further comprises all-metal support electronics for controlling access to the corresponding memory array module.

26. (Original) The display device of claim 24 wherein the memory array modules are arranged in two dimensions and stacked in a third dimension.

27. (Original) The display device of claim 1 wherein the all-metal electronics comprise a computer.

Please cancel claims 28-60 without prejudice.

61. (Original) A computer system, comprising at least one central processing unit, main memory, mass storage memory, a display device, display control electronics, and display memory, wherein the at least one central processing unit, the main memory, the mass storage memory, the display electronics, and the display memory are all implemented as all-metal electronics on a surface of the display device.

62. (Original) The computer system of claim 61 wherein the all-metal electronics comprise a plurality of transpinnors, each transpinnor comprising a network of multi-layer thin-film elements, at least one thin-film element in the transpinnor exhibiting giant magnetoresistance, the transpinnor further comprising a conductor magnetically coupled to the at least one thin-film element for controlling operation of the transpinnor, wherein the transpinnor is operable to generate an output signal which is a function of a resistive imbalance among the thin-film elements and which is substantially proportional to a power current in the network of thin-film elements.

63. (Original) The computer system of claim 61 wherein each of the main memory, the mass storage memory, and the display memory comprises a plurality of memory cells, each memory cell comprising a multi-layer structure exhibiting magnetoresistance.

64. (Original) The computer system of claim 63 wherein each multi-layer structure comprises:

a plurality of magnetic layers, at least one of the magnetic layers being for magnetically storing one bit of information; and

a plurality of the access lines integrated with the plurality of magnetic layers and configured such that the bit of information may be accessed using selected ones of the plurality of access lines and the giant magnetoresistive effect;

wherein the magnetic layers are part of substantially closed flux structure.